- Within incorporated towns and cities no two structures shall be spaced less than one hundred (100) feet apart.
- (d) The foregoing provisions for the spacing of signs do not apply to structures separated by buildings of other obstructions in such a manner that only one sign facing located within the above spacing distances is visible from the highway at any one time.
- (e) Official and "on-premise" signs and structures that are not lawfully maintained shall not be counted nor shall measurements be made from them for purposes of determining compliance with spacing requirements.
- (f) The minimum distance between structures shall be measured along the nearest edge of the pavement between points directly opposite the signs along each side of the highway and shall apply only to structures located on the same side of the highway.

## 3. Lighting of Signs-Restrictions -

- (a) Signs which contain, include, or are illuminated by any flashing, intermittent, or moving light or lights are prohibited, except those giving public service information such as time, date, temperature, weather, or similar information.
- (b) Signs which are not effectively shielded as to prevent beams or rays of light from being directed at any portion of the traveled ways of the Interstate or Federal-aid Primary Highway and which are of such intensity or brilliance as to cause glare and to impair the vision of the driver of any motor vehicle, or which otherwise interfere with any driver's operation of a motor vehicle are prohibited.
- (c) No sign shall be so illuminated that it interferes with the effectiveness of, or obscures an official traffic sign, device, or signal.